


PRODUCT NAME: AUTOGUARD S-4	CATALOGUE NO.: 06-000-0001 HOMOLOGATION NO.: E20 97RA-01 1541
---------------------------------------	--

Technical data:

	<ul style="list-style-type: none"> • supply method: constant, unbalanced voltage • maximal supply voltage: U_{Zmax}: 35 V • minimal supply voltage: U_{Zmin}: 8 V • current consumption in the operation mode: (at $U=12$ V): not greater than 40 mA • current consumption while standby: (at $U=12$ V): not greater than 20 mA • maximal current consumption (data transmission) by the supply voltage $U=12$ V: 500 mA • supply source: vehicle battery • operating temperature range (-40°C to +80°C) • housing dimensions: 67 x 48 x 36 mm • net weight: 0,2 kg
---	--

Functionality:

MAIN	<ul style="list-style-type: none"> • continuous communication using GPRS • communication via SMS • remote software changing • possibility of connection the semitrailer identification module
PROTECTION	<ul style="list-style-type: none"> • alarm lines monitoring • vehicle controlling possibility • anti-attack system • cooperating with ATWS factory mounted for Mercedes-Benz and Lexus
LOGISTICS	<ul style="list-style-type: none"> • fuel measurement • temperature measurement • speed measurement and determining localiaztion using GPS system • CAN - Bus (for the devices manufactured after 2005-08-01) • records buffer (out of GPRS range and in the roaming) • vehicle state control using analog and digital inputs